

CLIPPEDIMAGE= JP363213965A
PAT-NO: JP363213965A
DOCUMENT-IDENTIFIER: JP 63213965 A
TITLE: SEMICONDUCTOR DEVICE

PUBN-DATE: September 6, 1988

INVENTOR-INFORMATION:

NAME

ITOBAYASHI, MANABU

ASSIGNEE-INFORMATION:

NAME

MITSUBISHI ELECTRIC CORP

COUNTRY

N/A

APPL-NO: JP62049416

APPL-DATE: March 3, 1987

INT-CL_(IPC): H01L029/78; G01R031/30 ; H01L021/66

US-CL-CURRENT: 257/296,257/368

ABSTRACT:

PURPOSE: To facilitate a burn-in test, and to reduce cost by forming at least an insulating layer onto a gate electrode for a MOS transistor while shaping a conductive layer, which is arranged oppositely to at least the gate electrode and to which voltage is applied, onto the insulating layer.

CONSTITUTION: An insulating layer 6 has opening sections from which each partial surface of respective wiring layer 5G, 5S, 5D is exposed, and consists of a surface protective film coating separate electrode 5G, 5S, 5D and the upper surface of an inter-layer film 4. The layer 6 is shaped by an silicon oxide film or an silicon nitride film through a CVD method. A conductive layer 7 is positioned to the upper surface of the insulating layer 6 in the upper section of a gate electrode G, and formed by an aluminum film, etc. through a sputtering method in said region in which at least the gate electrode G is shaped. An electrode, which is formed by the same material as the conductive layer 7 and connected electrically and can be connected electrically to external terminals, is disposed, and high voltage is applied on a burn-in. One MOS transistor as a fundamental element is constituted of the gate electrode G,

a source electrode S and a drain electrode D.

COPYRIGHT: (C)1988,JPO&Japio

